

zenithinteriors.com

# VERSE 2

## Zenith

### Features:

Verse 2 offers a larger focus room, capable of comfortably catering to both an individual worker or a pair seeking a private setting within the open floor plan. It is fitted with a gallery rail to hang accessories, air ventilation & adjustable lighting. It can include a media panel and shelf for video conferencing, complemented by an optional SOL-Sit lounge across for seating.

Championing their sustainability commitment, Crafted Hardwoods will contribute to reforestation through OneTreePlanted for each Verse purchased with Crafted Hardwoods frames, For every Verse 2 sold, 2 trees will be planted.

### Options:

- 3 standard room sizes (WxD) with 2 available heights
- Media panel and shelf
- White board or cork board accessories

**Design:** ZENITH DESIGN STUDIO

**Warranty:** 5 years  
(Refer to Zenith Warranty Document for more details)

**Certifications:** GECA, 3 Green Star Credits for acoustics

### Finishes:

**Frame & Shelf:** Victorian Ash Timber, Crafted Hardwood Timber Tasmanian Oak & Blackbutt (Converted low value, juvenile pulp turned into new hardwoods that look and feel like 100-year-old wood)

**Shelf Option:** Natural White & Black Woodmatt Laminate

**Front Wall Panel:** Laminated Glass 6.76mm

**Glazed Door:** Frameless Toughened Glass 10mm

**Internal Side Walls:** Fabric or Sonic Board

**Internal Back Walls:** Laminated Glass 6.76mm, Fabric or Sonic Board

**External Side Walls:** Fabric

**External Back Walls:** Laminated Glass 6.76mm or Fabric

**Ceiling Internal:** Sonic Board


**Ceiling External:** Natural White Matt Laminate

**Inner/Outer Floor Track:** Black - Satin ZPC\_001


**Upholstery in fabric categories A, B, C, D, E and F**

Refer to Verse Fabric Specification


### Frame & Shelf:



### Sonic Board:



## Dimensions:



### Verse 2.1

OW 1980mm

OD 1380mm


H 2200/2400mm (Frame)

OH 2370/2600mm (Including fan box)

Internal Room Size: 1800 x 1200mm

Side walls made up of: 2x 600mmW panels

Front & back walls made up of: 2x 900mmW panels



### Verse 2.2

OW 1980mm

OD 1680mm


H 2200/2400mm (Frame)

OH 2370/2600mm (Including fan box)

Internal Room Size: 1800 x 1500mm

Side walls made up of: 1x 600mmW & 1x 900mmW panels

Front & back walls made up of: 2x 900mmW panels



### Verse 2.3

OW 1980mm

OD 1980mm

H 2200/2400mm (Frame)


OH 2370/2600mm (Including fan box)

Internal Room Size: 1800 x 1800mm

Side walls made up of: 2x 900mmW panels


Front & back walls made up of: 2x 900mmW panels

## Accessories:



### White Board or Cork Board with Black or Dark Brown Leather Strap


DIA: 600 & 900mm



### Gallery Rail


White board or cork board are easily  
attached and relocated

**Back Panel (Internal) Options:**




**Option 1**

Glass & Fabric or Sonic Board Panel



**Option 2**


Fabric or Sonic Board Panels



**Option 3**


Glass Panels

**Front Panel Options:**




**Option 1**

LH: Door Panel  
LH: Door Hinges  
RH: Glass Panel




**Option 2**

RH: Door Panel  
RH: Door Hinges  
LH: Glass Panel



**Option 3**


LH: Door Panel  
RH: Door Hinges  
RH: Glass Panel



**Option 4**

RH: Door Panel  
LH: Door Hinges  
LH: Glass Panel


**GPO Panel:**



**Left Hand Side**

Panel: 600/900mmW


- A1: 1175mmH
- A2: 945mmH
- B1: 805mmH
- B2: 605mmH
- B3: 165mmH



**Right Hand Side**

Mirrored

**Power Outlet Options:**



**GPO + HDMI + USB + DATA**



**2x GPO + HDMI + DATA**



**2x GPO + USB + DATA \***




**2x GPO + USB + HDMI**




**3x GPO + DATA \***



**3x GPO + HDMI**



**3x GPO + USB\***




**4x GPO\***

Note: \*not available as a power outlet option when a media panel has been selected.

## Media Panel: (Side Walls only)

TV & TV bracket not included



### Verse 2.1: Option 1A


Media Panel 2x 600mmW:

LH GPO, RH switch & RH shelf

Fabric or Sonic Board (Internal)

TV Bracket Height: 1175mm (Seated Level)

TV Size: 42" - 45"



### Verse 2.1: Option 1B


Media Panel 2x 600mmW:

RH GPO, LH switch & LH shelf

Fabric or Sonic Board (Internal)

TV Bracket Height: 1175mm (Seated Level)

TV Size: 42" - 45"



### Verse 2.2: Option 2A


Media Panel RH 600mmW & LH 900mmW:

LH GPO, RH switch & RH shelf

Fabric or Sonic Board (Internal)

TV Bracket Height: 1175mm (Seated Level)

TV Size: 42" - 65"



### Verse 2.2: Option 2B


Media Panel LH 600mmW & RH 900mmW:

RH GPO, LH switch & LH shelf

Fabric or Sonic Board (Internal)

TV Bracket Height: 1175mm (Seated Level)

TV Size: 42" - 65"



### Verse 2.3: Option 3A


Media Panel x2 900mmW:

LH GPO, RH switch & RH shelf

Fabric or Sonic Board (Internal)

TV Bracket Height: 1175mm (Seated Level)

TV Size: 42" - 65"



### Verse 2.3: Option 3B


Media Panel x2 900mmW:

RH GPO, LH switch & LH shelf

Fabric or Sonic Board (Internal)

TV Bracket Height: 1175mm (Seated Level)

TV Size: 42" - 65"




### Verse RH Shelf

OW 710mm

OD 330 & 180mm

OH 36mm

Installed Height: 720mm



### Verse LH Shelf

OW 710mm

OD 330 & 180mm

OH 36mm

Installed Height: 720mm

### Acoustics:


Verse has been tested in accordance with ISO 717-1:2004 Acoustics – Rating of sound insulation in buildings and of building elements – Airborne sound insulation.

Independent Acoustic Testing shows that Verse can qualify for 3 Green Star Credits for acoustics and can achieve between 28-36Dw at 40dB Ambiance with a Privacy Rating of 64-74, depending on the wall type and material selected.

Normal voice conversations can be heard as a muffled sound in adjoining rooms but cannot be understood.

Verse acoustic performance is comparable to most general use office rooms.

### Panel Layers:



### Air Ventilation:

Verse 2 has Induction airflow to give the larger room cleaner and better air exchange, with a maximum rating of 250-166L/s for 2-3 people in the space.



### Fire Safety:

The fire safety of all surface materials; timber, upholstery and acoustics materials used in Verse are tested and classified by either national or international standards.

No fire hazardous materials are used in the construction. Timber frames use BAL-19 Victorian Ash with natural fire resistance qualities (Higher rated Blackbutt BAL-29 can be used on request). Upholstered frame MDF substrate meets AS 3837, AS 1859.2 & AS 4266.16. Fabrics used in upholstery meets AS 3837 & ISO 5660-1. Interior and roof Sonic Boards meets EN 13501-1; B-s1,d0. Roof and wall acoustic insulation meets ISO 9705 & AS 5637.1. Laminate boards used in the roof meets AS 1859.2/3, AS 4266.13, AS 1539.3, and AS 3837.

The installation or relocation of Verse is not allowed to adversely impact on the regulatory requirements of a building. The location of Verse has to consider the location of exits and paths of travel to exits so as to not restrict the use or access of them.

Verse roof is adaptable to sprinklers and smoke detectors. Check with your local experts on the specific regulations, however if fire sprinklers are required in the booths a flexible pipe is to be used and at least 100mm of clearance above the ceiling to enable the roof to be lifted to gain access to services in the ceiling.


### Lighting:

Verse comes with 19W/m LED Strip Lighting and Driver suited for different room sizes with 1800lm/m Natural White (4000K).

Verse lighting brightness can be controlled by a dimmer, and turned off by PIR sensor when the room is unoccupied.

### Door / Light Switch Position:

All lighting components are compliant with Asia Pacific regional standards and certification requirements that include, EN 60598-1&2, AS61347.1&2, RCM, CE, RoHs and CCC.



Panel: 600/900mmW

Floor Height: 1050mm

Depth from left/right side: 100mm

External Swing door left or right side

Switch can be placed on left hand or right hand front panel

### Seismic Safety:

Verse can be anchored to the floor with bolts to keep the room upright in case of seismic activity. On request only. If Seismic is required, then depending on local Electrical Regulations alternative wiring looms may be required. Contact us for more information.