

NATTE

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella Acrylic		
Backing / Finish	Water-repellent & Stain-proof		
Weave	Braided 3/2		ISO 7211-1
Weight	275	g/m ²	ISO 3801
Width	140	cm	EN 1773
Roll length	50	m	

FABRIC RESISTANCE

Tensile strength	180	100	daN/5cm	ISO 13934-1
Elongation at break	24	28	%	ISO 13934-1
Pilling	4/5		Class / 5	ISO 12945-2
Spray test	5		Class / 5	ISO 4920
Oil-resistance properties	5		Class / 8	ISO 14419
Seam slippage (180 N)	<3	<5	mm	ISO 13936-2
Stitching strength	39.6	43	daN	ISO 13935-2
Stability on 40 deg. C washing	±1	±1	%	ISO 5077

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4/5	Class / 5	ISO 105 B04
Colour fastness UV - indoor	8	Class / 8	ISO 105 B02
Colour fastness under dry friction	5	Class / 5	ISO 105X12
Colour fastness under wet friction	5	Class / 5	ISO 105X12
Colour fastness 40°C washing	5	Class / 5	ISO 105 C06

FIRE RESISTANCE

California Technical Bulletin 117-203	Section 1
NFPA 260	Classe I
NF EN 1021-1	Non-Ignition

USES

Guarantee	5	years
Recommended Uses	seating, cushions, curtains	

CARE



This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration



Tested for harmful substances.
www.oeko-tex.com/standard100

